NSN 5905-00-279-2348

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-279-2348

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.562 inches
Shaft Length:
0.938 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.125 inches
Square Shaft Width:
0.188 inches
Shaft Style:
Square
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock or at 6 oclock or at 9 oclock or at 12 oclock
Nonturn Device Radius:
0.500 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
500.0 ohms single section
Power Dissipation Rating Per Section In Watts:
25.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Standard Taper Curve Per Section:

A single section

NSN 5905-00-279-2348

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Termi	nal	Type /	And	Quantity	=
3 tab.	sol	der lug	l		

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0