## NSN 5905-00-279-2360

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-279-2360

| Section Quantity:   |
|---|
| 1   |
| Body Style:   |
| Cylindrical bushing mounted                               |
| Reliability Indicator:                                    |
| Not established   |
| Body Diameter:  |
| 1.125 inches  |
| Shaft Diameter:   |
| 0.250 inches  |
| Shaft Length:   |
| 1.250 inches  |
| Mounting Bushing Length:                                  |
| 0.375 inches  |
| Body Length:  |
| 0.594 inches  |
| Shaft Style:  |
| Round   |
| Actuator Type:  |
| Single shaft  |
| Nonturn Device Location:                                  |
| At 3 oclock and at 9 oclock                               |
| Nonturn Device Radius:                                    |
| 0.531 inches  |
| Screw Thread Diameter:                                    |
| 0.375 inches  |
| Screw Thread Series Designator:                           |
| Unef  |
| Screw Thready Qty Per Inch (tpi):                         |
| 32.0  |
| Terminal Location:  |
| Radially positioned over less than half the circumference |
| Mounting Method:  |
| Standard bushing  |
| <b>Electrical Resistance Per Section:</b>                 |
| 150.0 ohms single section                                 |
| Power Dissipation Rating Per Section In Watts:            |
| 2.0 free air single section                               |
| Resistance Tolerance Per Section In Percent:              |
| -10.0 to 10.0 single section                              |

A single section

**Standard Taper Curve Per Section:** 

## NSN 5905-00-279-2360

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Terminal Type And Quantity: |
|-----------------------------|
| 3 tab, solder lug           |
| Shelf Life:                 |
| N/a                         |
| Unit Of Measure:            |

--

**Demilitarization:** No

A002a0

Fiig: