

View Online at <https://aerobasegroup.com/nsn/5905-00-279-2463>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

1.156 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

2.000 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

0.812 inches

**Shaft Style:**

Round

**Switch Type:**

Rotary

**Switch Voltage Rating In Volts:**

125.0

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 3 oclock and at 9 oclock

**Nonturn Device Radius:**

0.531 inches

**Switch Operating Position:**

Start of rotation

**Switch Contact Arrangement:**

Single pole, single throw, normally open, both positions maintained

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Features Provided:**

Switch

**Electrical Resistance Per Section:**

1.0 megohms single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

**Switch Current Type And Rating In Amps:**

2.000 ac/dc

**Standard Taper Curve Per Section:**

X single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0