Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-279-2481

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

### **Overall Length:**

1.957 inches

#### **Body Diameter:**

1.680 inches

#### Shaft Diameter:

Between 0.248 inches and 0.251 inches

## Shaft Length:

Between 0.453 inches and 0.547 inches

## Mounting Bushing Length:

Between 0.328 inches and 0.422 inches

## **Body Length:**

1.410 inches

## **Overall Diameter:**

2.260 inches

## Shaft Style:

Round, slotted

### Actuator Type:

Single shaft

## Maximum Starting Torque:

40.00 inch-ounces

#### Maximum Stop Torque:

240.00 inch-ounces

## Nonturn Device Location:

At 12 oclock

## Nonturn Device Radius:

Between 0.485 inches and 0.515 inches

#### Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

## Mounting Facility Quantity:

2

#### **Terminal Location:**

Radially positioned over less than half the circumference

Stops

N/a

No Fiig:

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



# **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 2.0 ohms single section **Rotary Actuator Travel In Angular Deg:** Between 275.0 and 305.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 340.0 single section **Power Dissipation Rating Per Section In Watts:** 25.0 heat sink single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Standard Taper Curve Per Section:** A single section **Test Data Document:** 81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 tab, solder lug **Specification Data:** 81349-mil-r-22/3 government specification Shelf Life: Unit Of Measure: **Demilitarization:** A002a0