## NSN 5905-00-279-2694

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-279-2694

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
2.312 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.688 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.375 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock and at 6 oclock and at 9 oclock and at 12 oclock
Nonturn Device Radius:
0.500 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
200.0 ohms single section
Power Dissipation Rating Per Section In Watts:
50.0 free air single section
Fixed Tap Quantity Per Section:
1 single section
Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

## NSN 5905-00-279-2694

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tap Location From Ccw Terminal Per Section In Ohms
100.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Special Features:** 

W/0.063 in. Diameter hole through shaft 5/32 in. From end and 4-36 by 1/4 in. Deep tap in end

**Terminal Type And Quantity:** 

4 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0