## NSN 5905-00-279-2698

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-279-2698 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 4.000 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.812 inches **Mounting Bushing Length:** 0.625 inches **Body Length:** 2.000 inches **Overall Diameter:** 4.281 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 1.25 kilohms single section **Power Dissipation Rating Per Section In Watts:** 150.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

**Standard Taper Curve Per Section:** 

A single section

## NSN 5905-00-279-2698

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal <sup>1</sup>	Гуре А	and Q	uantity:
-----------------------	--------	-------	----------

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0