Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-279-2702

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

### **Reliability Indicator:**

Not established

### **Body Diameter:**

4.000 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.500 inches

### Mounting Bushing Length:

0.375 inches

### Body Length:

### 2.000 inches

Shaft Style:

Round

Actuator Type:

Single shaft

### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## Mounting Method:

Standard bushing

## **Electrical Resistance Per Section:**

600.0 ohms single section

## Power Dissipation Rating Per Section In Watts:

150.0 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

# Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0