NSN 5905-00-279-2730

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-279-2730 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 3.000 inches **Shaft Diameter:** 0.375 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 2.625 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 200.0 kilohms single section **Power Dissipation Rating Per Section In Watts:** 12.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Standard Taper Curve Per Section:** A single section **Special Features:** 0.149 in. Dia. Mtg. Holes spaced 120 degrees apart on 0.875 in. Radius **Terminal Type And Quantity:** 3 threaded stud Shelf Life: N/a

Unit Of Measure:

NSN 5905-00-279-2730

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



em			

No

Fiig:

A002a0