Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-279-3071

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

### **Reliability Indicator:**

Not established

### First Flat Length:

0.375 inches

#### Flat Height:

0.219 inches

Body Diameter:

3.000 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.875 inches

### Mounting Bushing Length:

0.375 inches

**Body Length:** 

1.500 inches

#### Shaft Style:

Round, flatted

#### Actuator Type:

Single shaft

#### **Nonturn Device Location:**

At 3 oclock and at 6 oclock and at 9 oclock and at 12 oclock

#### Nonturn Device Radius:

0.500 inches

#### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

200.0 ohms single section

# Power Dissipation Rating Per Section In Watts:

100.0 free air single section



Resistance Tolerance Per Section In Percent: -20.0 to 20.0 single section Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: --Demilitarization:

No

Fiig:

A002a0