

View Online at <https://aerobasegroup.com/nsn/5905-00-279-4059>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.890 inches

Shaft Diameter:

Between 0.124 inches and 0.125 inches

Shaft Length:

Between 0.656 inches and 0.718 inches

Mounting Bushing Length:

Between 0.656 inches and 0.718 inches

Body Length:

0.765 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Maximum Starting Torque:

6.00 inch-ounces

Maximum Running Torque:

6.00 inch-ounces

Maximum Stop Torque:

32.00 inch-ounces

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.312 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

665.0 ohms all sections

Function Conformity Tolerance Per Section:

-1.00/+1.00 all sections

Power Dissipation Rating Per Section In Watts:

0.25 free air all sections

Function Conformity Per Section:

All sections absolute conformity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 all sections

Function Characteristic Per Section:

All sections equation

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 all sections

Test Data Document:

35351-151333 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0