NSN 5905-00-279-4169

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-279-4169

Section Quantity:				
1				
Body Style:				
Cylindrical bushing mounted				
Reliability Indicator:				
Not established				
Body Diameter:				
0.938 inches				
Shaft Diameter:				
0.250 inches				
Shaft Length:				
0.625 inches				
Mounting Bushing Length:				
0.375 inches				
Body Length:				
0.484 inches				
Shaft Style:				
Round, slotted				
Actuator Type:				
Single shaft				
Nonturn Device Location:				
At 3 oclock				
Nonturn Device Radius:				
0.438 inches				
Screw Thread Diameter:				
0.375 inches				
Screw Thread Series Designator:				
Unef				
Screw Thready Qty Per Inch (tpi):				
32.0				
Terminal Location:				
Radially positioned over less than half the circumference				
Mounting Method:				
Standard bushing w/shaft seal				
Electrical Resistance Per Section:				
1.0 megohms single section				
Power Dissipation Rating Per Section In Watts:				
0.5 free air single section				
Resistance Tolerance Per Section In Percent:				

A single section

-30.0 to 30.0 single section

Standard Taper Curve Per Section:

NSN 5905-00-279-4169

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal [•]	Type	And	Quantity:
-----------------------	------	-----	-----------

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0