NSN 5905-00-279-4200

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-279-4200

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.156 inches
Shaft Diameter:
0.250 inches
Shaft Length:
2.250 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.625 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock and at 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
Screw Thready Qty Per Inch (tpi): 32.0
32.0
32.0 Terminal Location:
32.0 Terminal Location: Radially positioned over less than half the circumference
32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method:
32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing
32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section:
32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 5.0 megohms single section
Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 5.0 megohms single section Power Dissipation Rating Per Section In Watts:

X single section

Standard Taper Curve Per Section:

NSN 5905-00-279-4200

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0