## NSN 5905-00-279-4213

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-279-4213

Section Overality
Section Quantity:
1
Reliability Indicator:
Not established
First Flat Length:
2.000 inches
Flat Height:
0.216 inches
Shaft Diameter:
0.250 inches
Shaft Length:
2.500 inches
Shaft Style:
Round, flatted
Switch Voltage Rating In Volts:
125.0
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock and at 9 oclock
Nonturn Device Radius:
0.531 inches
Switch Operating Position:
Switch Operating Position: Start of rotation
Start of rotation
Start of rotation  Switch Contact Arrangement:
Start of rotation  Switch Contact Arrangement:  Single pole, single throw, normally open, both positions maintained
Start of rotation  Switch Contact Arrangement:  Single pole, single throw, normally open, both positions maintained  Screw Thread Diameter:
Start of rotation  Switch Contact Arrangement:  Single pole, single throw, normally open, both positions maintained  Screw Thread Diameter:  0.375 inches
Start of rotation  Switch Contact Arrangement:  Single pole, single throw, normally open, both positions maintained  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:
Start of rotation  Switch Contact Arrangement:  Single pole, single throw, normally open, both positions maintained  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef
Start of rotation  Switch Contact Arrangement:  Single pole, single throw, normally open, both positions maintained  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):
Start of rotation  Switch Contact Arrangement:  Single pole, single throw, normally open, both positions maintained  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Electrical Resistance Per Section:
Start of rotation  Switch Contact Arrangement:  Single pole, single throw, normally open, both positions maintained  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Electrical Resistance Per Section:  100.000 kilohms single section
Start of rotation  Switch Contact Arrangement:  Single pole, single throw, normally open, both positions maintained  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Electrical Resistance Per Section:  100.000 kilohms single section  Power Dissipation Rating Per Section In Watts:
Start of rotation  Switch Contact Arrangement:  Single pole, single throw, normally open, both positions maintained  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Electrical Resistance Per Section:  100.000 kilohms single section
Start of rotation  Switch Contact Arrangement:  Single pole, single throw, normally open, both positions maintained  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Electrical Resistance Per Section:  100.000 kilohms single section  Power Dissipation Rating Per Section In Watts:  2.0 free air single section  Resistance Tolerance Per Section In Percent:
Start of rotation  Switch Contact Arrangement:  Single pole, single throw, normally open, both positions maintained  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Electrical Resistance Per Section:  100.000 kilohms single section  Power Dissipation Rating Per Section In Watts:  2.0 free air single section  Resistance Tolerance Per Section In Percent:  -10.0/+10.0 single section
Start of rotation  Switch Contact Arrangement:  Single pole, single throw, normally open, both positions maintained  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Electrical Resistance Per Section:  100.000 kilohms single section  Power Dissipation Rating Per Section In Watts:  2.0 free air single section  Resistance Tolerance Per Section In Percent:

5 tab, solder lug

## NSN 5905-00-279-4213

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0