NSN 5905-00-279-5057

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-279-5057 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.8750 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 2.000 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 2.000 inches **Mounting Hole Diameter:** 0.129 inches **Angle Of Mounting Hole In Deg:** 45.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 120.0 **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.375 inches **Body Length:** 1.020 inches **Mounting Lip Diameter:** 2.0160 inches **Mounting Lip Depth:** 0.0930 inches **Mounting Hole/stud Circle Diameter:** 1.250 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

356.0

NSN 5905-00-279-5057

Maximum Starting Torque:

Precision Wire Wound Variable Resistor - Page 2 of 3



0.80 inch-ounces
Maximum Running Torque:
0.60 inch-ounces
Shaft End Play:
0.005 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.006 inches
Pilot Diameter Runout:
0.00150 inches
Shaft Radial Play:
0.002 inches
Mounting Facility Quantity:
3
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
50.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section
85.0 single section
85.0 single section Power Dissipation Rating Per Section In Watts:
85.0 single section Power Dissipation Rating Per Section In Watts: 3.5 free air single section
85.0 single section Power Dissipation Rating Per Section In Watts: 3.5 free air single section Function Conformity Per Section:
85.0 single section Power Dissipation Rating Per Section In Watts: 3.5 free air single section Function Conformity Per Section: Single section independent linearity
85.0 single section Power Dissipation Rating Per Section In Watts: 3.5 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent:
85.0 single section Power Dissipation Rating Per Section In Watts: 3.5 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section
85.0 single section Power Dissipation Rating Per Section In Watts: 3.5 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section Actuator Travel Control Feature:
85.0 single section Power Dissipation Rating Per Section In Watts: 3.5 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section Actuator Travel Control Feature: Stops
85.0 single section Power Dissipation Rating Per Section In Watts: 3.5 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section Actuator Travel Control Feature: Stops Function Characteristic Per Section:
85.0 single section Power Dissipation Rating Per Section In Watts: 3.5 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear
Power Dissipation Rating Per Section In Watts: 3.5 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
85.0 single section Power Dissipation Rating Per Section In Watts: 3.5 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section

3 solder stud

NSN 5905-00-279-5057

Precision Wire Wound Variable Resistor - Page 3 of 3



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A002a0