## NSN 5905-00-279-5084

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-279-5084 **Section Quantity:** 2 **Body Style:** Cylindrical hole/slot mounted **Reliability Indicator:** Not established First Flat Length: 0.781 inches Flat Height: 0.344 inches **Body Diameter:** 5.000 inches **Shaft Diameter:** 0.375 inches **Shaft Length:** 1.562 inches **Body Length:** 5.812 inches **Mounting Hole/stud Circle Diameter:** 1.750 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 310.0 **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): **Mounting Facility Quantity: Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Threaded hole **Electrical Resistance Per Section:** 

2.5 ohms all sectionsRotary Actuator Travel In Angular Deg:310.0

## NSN 5905-00-279-5084

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 340.0 all sections **Power Dissipation Rating Per Section In Watts:** 225.0 free air all sections **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 all sections **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 all sections **Standard Taper Curve Per Section:** A all sections **Terminal Type And Quantity:** 6 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:** No