NSN 5905-00-279-8874

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-279-8874

0.01.00.0019
Section Quantity:
1
First Flat Length:
0.344 inches
Flat Height:
0.219 inches
Shaft Diameter:
0.250 inches
Shaft Length:
1.875 inches
Shaft Style:
Round, flatted
Switch Type:
Rotary
Switch Voltage Rating In Volts:
125.0
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock or at 6 oclock or at 9 oclock or at 12 oclock
Nonturn Device Radius:
0.500 inches
Switch Operating Position:
End of linear movement
Switch Contact Arrangement:
Single pole, single throw, normally open, both positions maintained
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
15.000 ohms single section
Power Dissipation Rating Per Section In Watts:
25.0 free air single section
Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

NSN 5905-00-279-8874

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Switch Current Type And Rating In Amps:
6.0000 ac/dc
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug and 2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0