## NSN 5905-00-279-8947

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-279-8947 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 0.968 inches **Body Diameter:** Between 0.835 inches and 0.855 inches **Mounting Bushing Length:** 0.445 inches **Body Length:** 0.280 inches **Overall Diameter:** Between 0.835 inches and 0.845 inches **Actuator Type:** Integral knob **Screw Thread Diameter:** 0.190 inches **Screw Thread Series Designator:** Unf Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 5.0 megohms single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

## NSN 5905-00-279-8947

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A002a0