NSN 5905-00-280-0522

Section Quantity:

Cylindrical bushing mounted

Reliability Indicator:

Body Style:

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-280-0522

Not established
Body Diameter:
0.750 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.375 inches
Shaft Style:
Round
Contact Arm Electrical Off Position:
Fully ccw
Actuator Type:
Single shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Screw Thread Series Designator: Unef
Unef
Unef Screw Thready Qty Per Inch (tpi):
Unef Screw Thready Qty Per Inch (tpi): 32.0
Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location:
Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference
Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method:
Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing
Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section:
Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 100.0 ohms single section
Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 100.0 ohms single section Function Conformity Tolerance Per Section:
Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 100.0 ohms single section Function Conformity Tolerance Per Section: -0.50/+0.50 single section
Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 100.0 ohms single section Function Conformity Tolerance Per Section: -0.50/+0.50 single section Power Dissipation Rating Per Section In Watts:
Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 100.0 ohms single section Function Conformity Tolerance Per Section: -0.50/+0.50 single section Power Dissipation Rating Per Section In Watts: 5.0 free air single section
Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 100.0 ohms single section Function Conformity Tolerance Per Section: -0.50/+0.50 single section Power Dissipation Rating Per Section In Watts: 5.0 free air single section Function Conformity Per Section:
Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 100.0 ohms single section Function Conformity Tolerance Per Section: -0.50/+0.50 single section Power Dissipation Rating Per Section In Watts: 5.0 free air single section Function Conformity Per Section: Single section independent linearity

NSN 5905-00-280-0522

Precision Wire Wound Variable Resistor - Page 2 of 2



Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0