## NSN 5905-00-280-1616

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-280-1616 **Section Quantity: Body Style:** Cylindrical hole/slot mounted **Reliability Indicator:** Not established First Flat Length: 0.344 inches Flat Height: 0.219 inches **Body Diameter:** 4.000 inches **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 2.000 inches **Mounting Hole/stud Circle Diameter:** 1.750 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity:** 2 **Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Unthreaded hole

## NSN 5905-00-280-1616

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
50.0 ohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
340.0 single section
Power Dissipation Rating Per Section In Watts:
150.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0