NSN 5905-00-283-2852

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-283-2852

-55.0/+105.0 Electrical Resistance: 583.000 ohms Resistance Tolerance in Percent: -0.250/+0.250 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 121.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+45.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 0.359 inches and 2.031 inches Body Length: Between 0.359 inches and 0.391 inches Body Length: Between 0.359 inches and 1.031 inches Power Dissipation Rating in Watts: 0.250 free air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Akida terminal each end Testa Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original squipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: Na Unit Of Measure:	
Electrical Resistance: 833.000 ohms Resistance Tolerance In Percent: -0.2504-0.250 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 121.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0f-85.0 Inclosure Wethod: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 0.359 inches and 2.031 inches Body Diameter: Between 0.359 inches and 0.391 inches Body Diameter: Between 0.359 inches and 1.031 inches Power Dissipation Rating in Watts: 0.250 fee air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Aktal terminal each end Test Data Document: 64859-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shell Life: Na Unit Of Measure: — Demilitarization: No Flig:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Sesistance Tolerance in Percent: -0.250/+0.250 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 121.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+85.0 Inclosure Method: Hermatically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Langth: Between 1.969 inches and 2.031 inches Bedoy Length: Between 0.359 inches and 0.391 inches Bedoy Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating in Watts: 0.250 free air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Akial terminal each end Test Data Document: 64959-9a51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit of Measure:	-55.0/ + 105.0
Resistance Tolerance in Percent: -0.250/-0.250 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 121.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -5.5.0/+8.5.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -5.5.0/+8.5.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.969 inches and 2.031 inches Body Diameter: Between 0.359 inches and 0.391 inches Body Length: Between 0.959 inches and 1.031 inches Power Dissipation Rating in Watts: 0.250 free air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Axial terminal each end Test Data Document: 64959-9361340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: Demilitarization: No Filig:	Electrical Resistance:
-0.250/40.250 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 121.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/485.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.969 inches and 2.031 inches Body Diameter: Between 0.359 inches and 0.391 inches Body Dameter: Between 0.359 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Axial terminal each end Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure:	583.000 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 121.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+85.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 0.359 inches and 2.031 inches Body Dlameter: Between 0.359 inches and 0.391 inches Body Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Axial terminal each end Test Data Document: Axial terminal each end Test Data Document: Axial terminal each ond Test Data Ocument: Axial terminal each ond or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 121.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.5.0/+95.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1,959 Inches and 2,031 inches Body Dlameter: Between 1,959 Inches and 0,331 inches Between 0,359 inches and 0,331 inches Between 0,959 inches and 1,031 inches Body Length: Between 0,969 inches and 1,031 inches Power Dissipation Rating In Watts: 0,250 free air Cubic Measure (non-core): 0,124 cubic inches Style Designator: Axial terminal each end Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: Demilitarization: No Filig:	-0.250/+0.250
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 121.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+85.0 Hermetically sealed Terminal Type: Wire laad Reliability Indicator: Not established Terminal Length: Between 1.969 inches and 2.031 inches Body Diameter: Between 0.369 inches and 0.391 inches Body Diameter: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Axial terminal each end Test Data Document: 64959-ga61340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.5.04-95.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1-969 inches and 2.031 inches Body Diameter: Between 1-969 inches and 0.391 inches Body Length: Between 0.959 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Axial terminal each end Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+85.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.969 inches and 2.031 inches Body Dameter: Between 0.359 inches and 0.391 inches Body Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Axial terminal each end Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.969 inches and 2.031 inches Body Diameter: Between 0.359 inches and 0.391 inches Body Diameter: Between 0.359 inches and 0.391 inches Body Length: Botween 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Avial terminal each end Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	121.0
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1,969 inches and 2,031 inches Body Diameter: Between 0,359 inches and 0,391 inches Body Length: Between 0,969 inches and 1,031 inches Power Dissipation Rating In Watts: 0,250 free air Cubic Measure (non-core): 0,124 cubic inches Style Designator: Axial terminal each end Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.969 inches and 2.031 inches Body Diameter: Between 0.359 inches and 0.391 inches Body Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Axial terminal each end Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-55.0/+85.0
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.969 inches and 2.031 inches Body Diameter: Between 0.359 inches and 0.391 inches Body Length: Between 0.369 inches and 1.031 inches Body Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Axial terminal each end Test Data Document: 64959-9a51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Terminal Length: Between 1.969 inches and 2.031 inches Body Diameter: Between 0.359 inches and 0.391 inches Body Length: Between 0.369 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Axial terminal each end Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Hermetically sealed
Reliability Indicator: Not established Terminal Length: Between 1.969 inches and 2.031 inches Body Diameter: Between 0.359 inches and 0.391 inches Body Length: Between 0.969 inches and 1.031 inches Body Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Axial terminal each end Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Note stablished Terminal Length: Between 1.969 inches and 2.031 inches Body Diameter: Between 0.359 inches and 0.391 inches Body Length: Between 0.969 inches and 1.031 inches Body Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Axial terminal each end Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Terminal Length: Between 1.989 inches and 2.031 inches Body Diameter: Between 0.359 inches and 0.391 inches Body Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Axial terminal each end Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
Between 1.999 inches and 2.031 inches Body Diameter: Between 0.359 inches and 0.391 inches Body Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Axial terminal each end Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Body Diameter: Between 0.359 inches and 0.391 inches Body Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Axial terminal each end Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Length:
Between 0.359 inches and 0.391 inches Body Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Axial terminal each end Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 1.969 inches and 2.031 inches
Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Axial terminal each end Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Axial terminal each end Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.359 inches and 0.391 inches
Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Axial terminal each end Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
0.250 free air Cubic Measure (non-core): 0.124 cubic inches Style Designator: Axial terminal each end Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.969 inches and 1.031 inches
Cubic Measure (non-core): 0.124 cubic inches Style Designator: Axial terminal each end Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
O.124 cubic inches Style Designator: Axial terminal each end Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 free air
Style Designator: Axial terminal each end Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Cubic Measure (non-core):
Axial terminal each end Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.124 cubic inches
Test Data Document: 64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	64959-ga51340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
Fiig:	No
	A001a0