

View Online at <https://aerobasegroup.com/nsn/5905-00-283-4264>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Overall Length:

1.500 inches

Body Diameter:

Between 0.430 inches and 0.570 inches

Shaft Diameter:

Between 0.123 inches and 0.126 inches

Shaft Length:

0.625 inches

Mounting Bushing Length:

Between 0.230 inches and 0.270 inches

Body Length:

0.650 inches

Overall Diameter:

Between 0.430 inches and 0.570 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

300.0

Maximum Starting Torque:

6.00 inch-ounces

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.187 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Electrical Resistance Per Section:

5.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

135.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 free air single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0