NSN 5905-00-283-4312

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-283-4312 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 4.188 inches **Body Diameter:** 1.062 inches **Shaft Diameter:** Between 0.248 inches and 0.251 inches **Shaft Length:** Between 2.984 inches and 3.016 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.188 inches **Overall Diameter:** 1.406 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 800.0 ohms 1st section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

NSN 5905-00-283-4312

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 1st section
Standard Taper Curve Per Section:
F 1st section
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0