## NSN 5905-00-283-4318

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-283-4318 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.391 inches **Body Diameter:** 1.156 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.125 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.266 inches **Overall Diameter:** 1.484 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Nonturn Device Location:** At 3 oclock and at 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing

**Electrical Resistance Per Section:** 

25.000 kilohms 1st section and 25.000 kilohms 2nd section

# NSN 5905-00-283-4318

Precision Nonwire Wound Variable Resistor - Page 2 of 2



### **Function Conformity Tolerance Per Section:**

-0.50/+0.50 all sections

### **Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

### **Function Conformity Per Section:**

Single section independent linearity

### **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 1st section and -10.0/+10.0 2nd section

#### **Function Characteristic Per Section:**

All sections linear

### **Terminal Type And Quantity:**

6 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

#### **Demilitarization:**

No

Fiig:

A002a0