Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-283-4357

#### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

1.656 inches

#### First Flat Length:

0.469 inches

#### Flat Height:

0.216 inches

#### Body Diameter:

1.125 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

1.000 inches

### Mounting Bushing Length:

0.375 inches

#### Body Length:

0.656 inches

#### Shaft Style:

Round, flatted

### Shaft Bearing Type:

Bearing

### Actuator Type:

Single shaft

### Nonturn Device Location:

At 3 oclock and at 9 oclock

### Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

2.500 megohms single section



Power Dissipation Rating Per Section In Watts:

2.0 free air single section

#### **Function Conformity Per Section:**

Single section independent linearity

## **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A002a0