

View Online at <https://aerobasegroup.com/nsn/5905-00-283-4361>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

1.000 inches

**Body Diameter:**

Between 0.859 inches and 0.891 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

0.450 inches

**Mounting Bushing Length:**

0.250 inches

**Body Length:**

Between 0.359 inches and 0.391 inches

**Shaft Style:**

Round

**Actuator Type:**

Double ended shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

320.0

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Locking bushing

**Electrical Resistance Per Section:**

100.0 ohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-700.0 to 700.0 single section

**Power Dissipation Rating Per Section In Watts:**

3.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-3.0 to 3.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

25.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0