

View Online at <https://aerobasegroup.com/nsn/5905-00-283-5167>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

1.156 inches

Shaft Diameter:

0.265 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.062 inches

Undercut Diameter:

0.375 inches

Shaft Style:

Round, stepped

Actuator Type:

Dual concentric

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Undercut Length:

0.188 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

500.0 kilohms 2nd section

Rotary Actuator Travel In Angular Deg:

3600.0

Power Dissipation Rating Per Section In Watts:

1.0 free air all sections

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 all sections

Actuator Travel Control Feature:

Clutch

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0