

View Online at <https://aerobasegroup.com/nsn/5905-00-283-5848>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

First Flat Length:

0.438 inches

Flat Height:

0.216 inches

Body Diameter:

2.312 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.000 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.375 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

300.0

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.500 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

150.0 ohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

Power Dissipation Rating Per Section In Watts:

50.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 15.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-6749 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 threaded stud

Specification Data:

81349-mil-r-6749 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0