NSN 5905-00-283-6474

Section Quantity:

Overall Length: 1.000 inches Shaft Diameter: 0.250 inches Shaft Length: 0.815 inches

Overall Diameter:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-283-6474

2.000 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
320.0
Maximum Starting Torque:
1.00 inch-ounces
Maximum Stop Torque:
0.50 inch-ounces
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
5.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
360.0
360.0 Function Conformity Tolerance Per Section:
360.0 Function Conformity Tolerance Per Section: -1.00/+1.00 single section
360.0 Function Conformity Tolerance Per Section: -1.00/+1.00 single section Power Dissipation Rating Per Section In Watts:
360.0 Function Conformity Tolerance Per Section: -1.00/+1.00 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section
Function Conformity Tolerance Per Section: -1.00/+1.00 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section Function Conformity Per Section:
Function Conformity Tolerance Per Section: -1.00/+1.00 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section Function Conformity Per Section: Single section independent linearity
Function Conformity Tolerance Per Section: -1.00/+1.00 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent:
Function Conformity Tolerance Per Section: -1.00/+1.00 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section
Function Conformity Tolerance Per Section: -1.00/+1.00 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section Actuator Travel Control Feature:
Function Conformity Tolerance Per Section: -1.00/+1.00 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section Actuator Travel Control Feature: Continuous motion
Function Conformity Tolerance Per Section: -1.00/+1.00 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section:
Function Conformity Tolerance Per Section: -1.00/+1.00 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear

NSN 5905-00-283-6474

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A002a0