NSN 5905-00-283-7374

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-283-7374 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 4.312 inches **Body Diameter:** 3.312 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.500 inches **Mounting Bushing Length:** 0.438 inches **Body Length:** Between 2.781 inches and 2.844 inches **Overall Diameter:** 3.688 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 5400.0 **Maximum Starting Torque:** 2.70 inch-ounces **Maximum Running Torque:** 2.00 inch-ounces **Maximum Stop Torque:** 1150.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Shaft End Play:**

0.007 inches **Shaft Runout:** 0.0005 inches

NSN 5905-00-283-7374

Precision Wire Wound Variable Resistor - Page 2 of 3



Lateral Runout:
0.003 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.003 inches
Screw Thread Diameter:
0.500 inches
Screw Thread Series Designator:
Uns
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
5400.0
Function Conformity Tolerance Per Section:
-0.50/+0.05 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
10.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-0.0/+130.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 tab, solder lug

N/a

Shelf Life:

NSN 5905-00-283-7374

Precision Wire Wound Variable Resistor - Page 3 of 3



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0