## NSN 5905-00-283-7437

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-283-7437

On other Occasillar						
Section Quantity:						
Body Style:						
Cylindrical bushing mounted						
Reliability Indicator:						
Not established						
First Flat Length:						
0.281 inches						
Flat Height:						
0.156 inches						
Body Diameter:						
1.625 inches						
Shaft Diameter:						
0.250 inches						
Shaft Length:						
0.344 inches						
Mounting Bushing Length:						
0.281 inches						
Body Length:						
0.562 inches						
Shaft Style:						
Round, flatted						
Actuator Type:						
Single shaft						
Screw Thread Diameter:						
0.375 inches						
Screw Thread Series Designator:						
Unef						
Screw Thready Qty Per Inch (tpi):						
32.0						
Terminal Location:						
Radially positioned over less than half the circumference						
Mounting Method:						
Standard bushing						
Electrical Resistance Per Section:						
75.0 ohms single section						
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:						
340.0 single section						
Power Dissipation Rating Per Section In Watts:						
4.0 free air single section						
Resistance Tolerance Per Section In Percent:						
-10.0 to 10.0 single section						

## NSN 5905-00-283-7437

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient	Tempura	ture In	Deg C	elsius	Per S	Section A	At Full	Rated	Power:

40.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_\_

Demilitarization:

No

Fiig:

A002a0