NSN 5905-00-283-8153

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-283-8153

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.938 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.750 inches
Body Length:
0.453 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
300.0
Nonturn Device Location:
At 3 oclock and at 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
300.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

NSN 5905-00-283-8153

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No