NSN 5905-00-283-8173

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-283-8173 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.250 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.188 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.188 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 280.0 **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 Radially positioned over less than half the circumference

Terminal Location:
Radially positioned over less than half the circumference

Mounting Method:
Standard bushing
Electrical Resistance Per Section:
5.0 kilohms 2nd section
Rotary Actuator Travel In Angular Deg:
280.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 all sections

NSN 5905-00-283-8173

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Dever Dissingtion Bating Pay Section in Watter
Power Dissipation Rating Per Section In Watts:
3.0 free air all sections
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 all sections
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No