Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-283-8780

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

### **Body Diameter:**

0.875 inches

#### Shaft Diameter:

0.250 inches

Shaft Length:

Between 0.359 inches and 0.391 inches

## Mounting Bushing Length:

0.250 inches

## Body Length:

0.656 inches

#### Shaft Style:

Round, slotted

### Actuator Type:

Single shaft

## Nonturn Device Location:

At 9 oclock

### Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

#### **Mounting Method:**

Standard bushing

#### **Electrical Resistance Per Section:**

10.0 ohms single section

## Power Dissipation Rating Per Section In Watts:

2.0 free air single section

## **Resistance Tolerance Per Section In Percent:**

-20.0 to 5.0 single section

## Standard Taper Curve Per Section:

A single section

### **Terminal Type And Quantity:**

3 tab, solder lug

# NSN 5905-00-283-8780

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0