NSN 5905-00-283-8852

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-283-8852 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.0750 inches Pilot Length: 0.1000 inches **Undercut Diameter:** 2.750 inches **Undercut Width:** 0.1550 inches **Body Diameter:** 3.000 inches **Angle Of Mounting Hole In Deg:** 90.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 120.0 **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.750 inches **Body Length:** 1.281 inches **Mounting Lip Diameter:** 3.7500 inches **Mounting Lip Depth:** 0.0750 inches **Mounting Hole/stud Circle Diameter:** 1.500 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Maximum Starting Torque:**

1.00 inch-ounces

Maximum Running Torque:

0.50 inch-ounces

NSN 5905-00-283-8852

Precision Wire Wound Variable Resistor - Page 2 of 2



| Screw Thread Diameter: |
|---|
| 0.164 inches |
| Screw Thread Series Designator: |
| Unc |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Mounting Facility Quantity: |
| 3 |
| Terminal Location: |
| Radially positioned over less than half the circumference |
| Mounting Method: |
| Threaded hole |
| Features Provided: |
| Nonmetallic shaft |
| Electrical Resistance Per Section: |
| 7.2 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 360.0 |
| Function Conformity Tolerance Per Section: |
| -0.15/+0.15 single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 85.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 6.0 free air single section |
| Function Conformity Per Section: |
| Single section independent linearity |
| Resistance Tolerance Per Section In Percent: |
| -10.0/+10.0 single section |
| Actuator Travel Control Feature: |
| Continuous motion |
| Function Characteristic Per Section: |
| Single section linear |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 40.0 single section |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |
| Fiig: |

A002a0