Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-283-8855

## Section Quantity:

1

Body Style:

Cylindrical studs mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

2.625 inches

#### Body Diameter:

2.750 inches

## Shaft Diameter:

0.375 inches

### Shaft Length:

1.000 inches

### Body Length:

2.000 inches

## **Overall Diameter:**

3.000 inches

## Mounting Hole/stud Circle Diameter:

0.875 inches

### Shaft Style:

Round

### Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

360.0

### Screw Thread Diameter:

0.138 inches

### **Screw Thread Series Designator:**

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Mounting Facility Quantity:**

3

### **Terminal Location:**

Radially positioned over less than half the circumference

### **Mounting Method:**

Threaded hole

## **Features Provided:**

Nonmetallic shaft

### **Electrical Resistance Per Section:**

25.0 kilohms single section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



**Rotary Actuator Travel In Angular Deg:** 360.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 11.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0

---