NSN 5905-00-284-2586

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-284-2586

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
First Flat Length:
0.266 inches
Flat Height:
0.186 inches
Body Diameter:
1.266 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.719 inches
Mounting Bushing Length:
0.281 inches
Body Length:
0.688 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock and at 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.0 kilohms single section
•
Power Dissipation Rating Per Section In Watts:

2.0 free air single section

NSN 5905-00-284-2586

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance	Tolerance	Per	Section	In	Percent:

-10.0/+10.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0