NSN 5905-00-284-3833

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-284-3833 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.8250 inches Pilot Length: 0.0620 inches **Overall Length:** 1.938 inches **Undercut Diameter:** 1.875 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 2.000 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.938 inches **Body Length:** 1.000 inches **Mounting Lip Diameter:** 2.0000 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 320.0 **Maximum Starting Torque:** 0.60 inch-ounces **Maximum Running Torque:**

0.30 inch-ounces Shaft End Play:

0.00300 inches

NSN 5905-00-284-3833

Shaft Runout:

Precision Wire Wound Variable Resistor - Page 2 of 3



0.001 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.00150 inches
Shaft Radial Play:
0.002 inches
Mechanical Backlash In Deg Angular Rotation:
10.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
20.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-1.0/+1.0 ohms single section
Resistance Tolerance Per Section In Percent:
-1.0/+1.0 single section
Actuator Travel Control Feature:
Stops
Tap Location From Ccw Terminal Per Section In Ohms:
10000.0 single section
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a

NSN 5905-00-284-3833

Precision Wire Wound Variable Resistor - Page 3 of 3



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A002a0