

0-284-3999

	Nonprecision Wire Wound Variable Resis
,	View Online at https://aerobasegroup.com/nsn/5905-00
;	Section Quantity:
	1
I	First Flat Length:
(	0.344 inches
I	Flat Height:
(	0.219 inches
;	Shaft Diameter:
(	0.250 inches
ę	Shaft Length:
	2.500 inches
I	Mounting Bushing Length:
(	0.375 inches
;	Shaft Style:
ļ	Round, flatted
	Actuator Type:
ę	Single shaft
I	Nonturn Device Location:
1	At 12 oclock
I	Nonturn Device Radius:
(	0.500 inches
ę	Screw Thread Diameter:
(	0.375 inches
ę	Screw Thread Series Designator:
I	Unef
ę	Screw Thready Qty Per Inch (tpi):
;	32.0
I	Mounting Method:
ļ	Standard bushing
I	Electrical Resistance Per Section:
;	350.000 ohms single section
l	Power Dissipation Rating Per Section In Watts:
	25.0 free air single section
I	Function Conformity Per Section:
ę	Single section independent linearity
I	Resistance Tolerance Per Section In Percent:
	10.0 to 10.0 single section
ę	Standard Taper Curve Per Section:
1	A single section
•	Terminal Type And Quantity:
	3 tab, solder lug
;	Shelf Life:
I	N/a

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0