

View Online at <https://aerobasegroup.com/nsn/5905-00-287-9929>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

20.5 millimeters

Body Diameter:

16.0 millimeters

Shaft Diameter:

3.2 millimeters

Shaft Length:

10.0 millimeters

Mounting Bushing Length:

6.0 millimeters

Body Length:

10.0 millimeters

Overall Diameter:

31.5 millimeters

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Switch Type:

Rotary

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Switch Contact Arrangement:

Single pole, single throw, normally open, both positions maintained

Screw Thread Diameter:

6.0 millimeters

Screw Thread Series Designator:

Iso m

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Switch

Electrical Resistance Per Section:

10.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

Power Dissipation Rating Per Section In Watts:

0.1 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0