Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-289-9856

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Overall Length:**

2.766 inches

### First Flat Length:

0.500 inches

Flat Height:

Between 0.107 inches and 0.111 inches

### **Body Diameter:**

0.637 inches

#### Shaft Diameter:

0.136 inches

### Shaft Length:

1.438 inches

# Mounting Bushing Length:

0.250 inches

# Body Length:

0.578 inches

#### **Overall Diameter:**

0.637 inches

### Shaft Style:

Round, flatted

Switch Type:

Rotary

# Switch Voltage Rating In Volts:

125.0

#### Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

1800.0

# Nonturn Device Location:

At 9 oclock

# Nonturn Device Radius:

0.375 inches

# Switch Operating Position:

Start of rotation

# Switch Contact Arrangement:

Single pole, single throw, normally closed



Fragility Factor:	
Rugged	
Screw Thread Diameter:	
0.250 inches	
Screw Thread Series Designator:	
Unef	
Screw Thready Qty Per Inch (tpi):	
32.0	
Terminal Location:	
Rear-bottom	
Mounting Method:	
Standard bushing	
Features Provided:	
Switch	
Electrical Resistance Per Section:	
200.0 ohms single section	
Rotary Actuator Travel In Angular Deg:	
1800.0	
Ambient Tempurature In Deg Celsius Per Section A	t Zero Percent Rated Power:
100.0 single section	
Tempurature Coefficient Of Resistance Per Section	In Ppm Per Deg Celsius:
-3000.0 to 3000.0 single section	
Power Dissipation Rating Per Section In Watts:	
0.3 free air single section	
Resistance Tolerance Per Section In Percent:	
-30.0 to 30.0 single section	
Actuator Travel Control Feature:	
Stops	
Ambient Tempurature In Deg Celsius Per Section A	t Full Rated Power:
50.0 single section	
Switch Current Type And Rating In Amps:	
1.000 ac	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
5 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A002a0	