## NSN 5905-00-295-3483

**Section Quantity:** 

Cylindrical bushing mounted

Reliability Indicator:

**Body Style:** 

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-295-3483

Not established
Overall Height:
1.219 inches
Overall Width:
0.969 inches
Body Diameter:
0.969 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.500 inches
Body Length:
0.469 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.000 kilohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section

## NSN 5905-00-295-3483

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power	Dissipation	Rating Po	er Section	In Watts:
	DISSIDATION	ivatilid i	ei occiion	III vvaiis.

1.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-20.0 to 20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A002a0