Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-295-3489

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

## **Body Diameter:**

0.312 inches

## Shaft Diameter:

0.125 inches

#### Shaft Length:

0.500 inches

## Mounting Bushing Length:

0.375 inches

## Body Length:

## 0.500 inches

Shaft Style:

## Round

Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

360.0

## Nonturn Device Location:

At 3 oclock and at 9 oclock

## Nonturn Device Radius:

0.375 inches

## Screw Thread Diameter:

0.250 inches

## Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# **Mounting Method:**

Standard bushing

# **Electrical Resistance Per Section:**

5.000 kilohms single section

# Rotary Actuator Travel In Angular Deg:

360.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

# NSN 5905-00-295-3489 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

0.5 free air single section

## **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

## Actuator Travel Control Feature:

Continuous motion

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

## Unit Of Measure:

--

# Demilitarization:

No

## Fiig:

A002a0