Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-295-3775

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

0.938 inches

#### Body Diameter:

0.625 inches

#### Shaft Diameter:

0.125 inches

#### Shaft Length:

0.500 inches

#### Mounting Bushing Length:

## 0.375 inches

**Body Length:** 

0.438 inches

#### **Overall Diameter:**

0.734 inches

## Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

## Nonturn Device Location:

At 9 oclock

#### **Nonturn Device Radius:**

0.234 inches

#### Screw Thread Diameter:

0.250 inches

#### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

5.0 kilohms single section

# Power Dissipation Rating Per Section In Watts:

0.2 free air single section



Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0