NSN 5905-00-295-3784

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-295-3784

Section Quantity:
2

Body Style:

Cylindrical bushing mounted Reliability Indicator:

Not established

Shaft Diameter:

Between 0.249 inches and 0.251 inches

Shaft Length:

0.750 inches

Body Length:

0.969 inches

Shaft Style:

Round

Actuator Type:

Dual concentric

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.515 inches and 0.547 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

25.000 kilohms 2nd section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 1st section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

NSN 5905-00-295-3784

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0