NSN 5905-00-295-3849

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-295-3849

Section Quantity:					
1					
Reliability Indicator:					
Not established					
Shaft Diameter:					
0.250 inches					
Shaft Length:					
0.625 inches					
Mounting Bushing Length:					
0.500 inches					
Shaft Style:					
Round, slotted					
Shaft Bearing Type:					
Bearing					
Actuator Type:					
Single shaft					
Nonturn Device Location:					
At 3 oclock and at 9 oclock					
Nonturn Device Radius:					
0.438 inches					
Screw Thread Diameter:					
0.375 inches					
Screw Thread Series Designator:					
Unef					
Screw Thready Qty Per Inch (tpi):					
32.0					
Mounting Method:					
Standard bushing					
Electrical Resistance Per Section:					
500.000 kilohms single section					
Power Dissipation Rating Per Section In Watts:					
1.0 free air single section					
Function Conformity Per Section:					
Single section independent linearity					
Resistance Tolerance Per Section In Percent:					
-20.0 to 20.0 single section					
Standard Taper Curve Per Section:					
A single section					
Terminal Type And Quantity:					
3 tab, solder lug					
Shelf Life:					
N/a					

NSN 5905-00-295-3849

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



	• -			
In	ıŧ	()t	Measure	•

--

Demilitarization:

No

Fiig:

A002a0