Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-295-5011

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-30.0/+30.0

**Electrical Resistance:** 

34.000 ohms

**Resistance Tolerance In Percent:** 

-1.000/+1.000

Heat Sink Material:

Aluminum alloy

Heat Sink Length:

6.000 inches

Heat Sink Width:

4.000 inches

**Heat Sink Height:** 

2.000 inches

Heat Sink Thickness:

### 0.040 inches

Ambient Tempurature In Deg Celsius At Full Rated Power:

25.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

275.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+275.0

### Inclosure Method:

Encased

#### **Terminal Type:**

Tab, solder lug

**Reactance Characteristic:** 

Noninductive

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.010

Terminal Length:

0.266 inches

Body Length:

0.600 inches

# Body Width:

0.334 inches

Body Height:

0.320 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.444 inches

Wire Wound Fixed Resistor - Page 2 of 2



**Power Dissipation Rating In Watts:** 

3.000 free air

Mounting Hole Size:

0.093 inches

Style Designator:

Axial terminal (s)

# Test Data Document:

81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-r-39009/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0