Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-295-5871

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## Body Diameter:

1.093 inches

### Shaft Diameter:

0.250 inches

#### Shaft Length:

2.500 inches

#### Mounting Bushing Length:

0.375 inches

#### Body Length:

0.562 inches

#### Shaft Style:

Round

# Actuator Type:

Single shaft

### Nonturn Device Location:

At 9 oclock

### Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

#### **Mounting Method:**

Standard bushing

#### **Electrical Resistance Per Section:**

2.500 kilohms single section

#### **Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

### **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

## **Terminal Type And Quantity:**

3 tab, solder lug

#### Shelf Life:

N/a



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0