

View Online at <https://aerobasegroup.com/nsn/5905-00-295-5988>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

2.297 inches

Shaft Diameter:

0.234 inches

Shaft Length:

2.250 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.812 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

295.0

Maximum Starting Torque:

6.00 inch-ounces

Nonturn Device Location:

At 3 oclock and at 9 oclock and at 3 oclock and at 9 oclock

Nonturn Device Radius:

Between 0.188 inches and 0.219 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Grounded contact arm

Electrical Resistance Per Section:

3500.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

307.0

Power Dissipation Rating Per Section In Watts:

7.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Stops

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0