## NSN 5905-00-296-8308

Nonprecision Wire Wound Variable Resistor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5905-00-296-8308



**Section Quantity: Body Style:** Cylindrical bushing mounted **Overall Length:** 1.261 inches **Terminal Length:** 0.485 inches **Body Diameter:** Between 1.581 inches and 1.602 inches **Shaft Diameter:** Between 0.248 inches and 0.251 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.500 inches **Body Length:** Between 0.611 inches and 0.636 inches **Overall Diameter:** 2.087 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 280.0 and 305.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Stop Torque:** 30.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference

## NSN 5905-00-296-8308

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Mounting Method: Locking bushing Features Provided: Nonmetallic shaft Electrical Resistance Per Section: 8.000 ohms single section Rotary Actuator Travel In Angular Deg: Between 280.0 and 305.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
Features Provided: Nonmetallic shaft  Electrical Resistance Per Section: 8.000 ohms single section  Rotary Actuator Travel In Angular Deg: Between 280.0 and 305.0  Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section  Power Dissipation Rating Per Section In Watts: 4.0 free air single section  Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section  Actuator Travel Control Feature:  Stops  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
Ronmetallic shaft  Electrical Resistance Per Section: 8.000 ohms single section  Rotary Actuator Travel In Angular Deg: Between 280.0 and 305.0  Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section  Power Dissipation Rating Per Section In Watts: 4.0 free air single section  Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section  Actuator Travel Control Feature:  Stops  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
Electrical Resistance Per Section:  8.000 ohms single section  Rotary Actuator Travel In Angular Deg:  Between 280.0 and 305.0  Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:  105.0 single section  Power Dissipation Rating Per Section In Watts:  4.0 free air single section  Resistance Tolerance Per Section In Percent:  -10.0 to 10.0 single section  Actuator Travel Control Feature:  Stops  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
8.000 ohms single section  Rotary Actuator Travel In Angular Deg:  Between 280.0 and 305.0  Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:  105.0 single section  Power Dissipation Rating Per Section In Watts:  4.0 free air single section  Resistance Tolerance Per Section In Percent:  -10.0 to 10.0 single section  Actuator Travel Control Feature:  Stops  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
Rotary Actuator Travel In Angular Deg:  Between 280.0 and 305.0  Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:  105.0 single section  Power Dissipation Rating Per Section In Watts:  4.0 free air single section  Resistance Tolerance Per Section In Percent:  -10.0 to 10.0 single section  Actuator Travel Control Feature:  Stops  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
Between 280.0 and 305.0  Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:  105.0 single section  Power Dissipation Rating Per Section In Watts:  4.0 free air single section  Resistance Tolerance Per Section In Percent:  -10.0 to 10.0 single section  Actuator Travel Control Feature:  Stops  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:  105.0 single section  Power Dissipation Rating Per Section In Watts:  4.0 free air single section  Resistance Tolerance Per Section In Percent:  -10.0 to 10.0 single section  Actuator Travel Control Feature:  Stops  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
Power Dissipation Rating Per Section In Watts: 4.0 free air single section  Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section  Actuator Travel Control Feature: Stops  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
Power Dissipation Rating Per Section In Watts:  4.0 free air single section  Resistance Tolerance Per Section In Percent:  -10.0 to 10.0 single section  Actuator Travel Control Feature:  Stops  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
4.0 free air single section  Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section  Actuator Travel Control Feature: Stops  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
-10.0 to 10.0 single section  Actuator Travel Control Feature:  Stops  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
40.0 single section	
Standard Taper Curve Per Section:	
A single section	
Test Data Document:	
81349-mil-r-19/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification f	rmat
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment	al
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Terminal Type And Quantity:	
3 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A002a0	