NSN 5905-00-299-4427

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-299-4427 **Section Quantity:** 1 **Body Style:** Rectangular w/bushing/slot mounted **Reliability Indicator:** Not established **Mounting Hole Diameter:** 0.093 inches **Shaft Diameter:** 0.093 inches **Shaft Length:** 0.344 inches **Mounting Bushing Length:** 0.281 inches **Body Length:** 0.578 inches **Body Width:** 0.190 inches **Body Height:** 0.609 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 15120.0 **Lateral Distance Between Mounting Hole Centers:** 0.520 inches **Screw Thread Diameter:** 0.190 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:**

Standard bushing and unthreaded hole

Electrical Resistance Per Section:

100.0 ohms single section

NSN 5905-00-299-4427

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
15120.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: